Claims

1.   A system for driving a compressor, comprising
      an induction motor (2) for driving the compressor
5   (3a), said induction motor including a squirrel cage
rotor, and
      a controller (1) for controlling the induction
motor, said controller comprising
      a memory (47) for storing drive patterns for driving
10   the induction motor,
      a first frequency generation means (43) for
generating a field frequency based on a field command
and/or
      a second frequency generation means (44) for
15   generating a voltage frequency based on a voltage
command,
      wherein a drive pattern is extracted from the memory
based on the generated frequency or frequencies.

20   2.   The system according to claim 1, wherein the
controller comprises a processing means (42) for
generating the field command and/or the voltage command
based on an input request.

25   3.   The system according to claim 1, wherein the
controller is adapted to distinguish between a steady
state and a transient state of the induction motor.

      4.   The system according to claim 3, wherein the
30   processing means (42) is adapted to generate the field
command and/or the voltage command depending on the state
of the induction motor.

5.   The system according to claim 4, wherein the field command and/or voltage command is generated based on look-up tables.

5   6.   The system according to claim 4, wherein the field command and/or voltage command is generated based on a model based control.

7.   A system for driving a compressor, comprising

10   an induction motor (2) for driving for driving the compressor (3a), said induction motor including a squirrel cage rotor, and

          a controller (1) for controlling the induction motor, wherein the controller is adapted to distinguish

15   between a steady state and a transient state of the induction motor.

8.   The system according to claim 7, wherein the controller is adapted to control the induction motor

20   depending on the state of the induction motor.

9.   The system according to claim 8, wherein the controller generates a field command and/or a voltage command dependent on the state of the induction motor.

25

10.   The system according to claim 9, wherein the field command and/or voltage command is generated based on look-up tables.

30   11.   The system according to claim 9, wherein the field command and/or voltage command is generated based on a model based control.

12.   The system according to claim 7, wherein the

35   controller comprises

- 27 -

a memory (47) for storing drive patterns for the induction motor,

a first frequency generation means (43) for generating a field frequency based on a field command

5   and/or

a second frequency generation means (44) for generating a voltage frequency based on a voltage command,

wherein a drive pattern is extracted from the memory

10   based on the generated frequency or frequencies.

13. The system according to claim 12, wherein the controller comprises a processing means (42) for generating the field command and/or the voltage command

15   based on an input request.

14. The system according to claim 1 or 12, wherein the first and/or the second frequency generation means (43, 44) is a voltage controlled oscillator.

20

15. The system according to claim 1 or 12, further comprising a counter (45, 46) receiving the frequency output of the frequency generation means (43, 44),

wherein the counter is adapted to count a value

25   based on the frequency of the frequency generation means, and

the frequency is used as an address for accessing the memory (47).

30   16. The system according to claim 1 or 12, wherein the first frequency generation means (43) for generating the field frequency and the second frequency generation means (44) for generating a voltage frequency is used, wherein

the memory (47) is accessed by using a first address and a second address, and the system further comprises a first counter (45) and a second counter (46), wherein

5   the first counter is adapted to count a value based on the frequency of the first frequency generation means, and the second counter is adapted to count a value based on the frequency of the second frequency generation means, wherein

the count value of the first frequency generation
10   means is used as the first address, and the count value of the second frequency generation means is used a second address.

17.   The system according to claim 16, wherein one of the
15   first and second addresses is a column address, and the other address of the first and second addresses is a line address.

18.   The system according to any of the claims 1 to 17,
20   wherein the compressor (3a) is a part of a turbocharger (3).

19.   The system according to any of the claims 1 to 17, wherein the compressor is an electrically driven
25   compressor.

20.   The system according to any of the claims 1 to 17, wherein the compressor is part of an electrically assisted turbocharger.

30